

A22060 Series

Dia 220X60mm(Dia 8.60"X2.36")



HOUSING	Die - Cast Aluminum, Painted Black
IMPELLER	Thermoplastic PBT, UL94V-0
BEARING	Ball
TERMINATION	Lead Wire
OPERATING VOLTAGE RANGE	/
DIELECTRIC STRENGTH	1,500 VAC for 1 minute
INSULATION	Class B
INSULATION RESISTANCE	100,000 Ohms min. @ 500VDC
OPERATING TEMPERATURE	-20 °C TO + 80 °C
SAFETY	Impedance Protected
WEIGHT	1.4kg

MODEL NO.	RATED VOLTAGE (V)	FREQUENCY (Hz)	RATED CURRENT (A)	INPUT POWER (W)	SPEED RPM	MAX. AIR PRESSURE		AIR FLOW		NOISE dB(A) @1M
						InchH ₂ O	mmH ₂ O	m ³ /min	CFM	
A22060V1H	115	50/60	0.9/0.8	60/57	2300/2100	0.9/0.8	22.86/20.32	11.3/10.2	399/360	58/56
A22060V2H	230	50/60	0.9/0.8	49/50	2300/2100	0.9/0.8	22.86/20.32	11.3/10.2	399/360	58/56

